

2.4M C & Ku-Band Rx/Tx Antenna

Series 1241

Technical Specifications

Electrical		C-Band Linear	C-Band Circular	Ku-Band
Antenna Size		2.4M (96 in.)	2.4M (96 in.)	2.4M (96 in.)
Operating Frequency (GHz)	Receive	3.625 - 4.20 GHz	3.625 - 4.20 GHz	10.70 - 12.75 GHz
	Transmit	5.85 - 6.425 GHz	5.85 - 6.425 GHz	13.75 - 14.50 GHz
Antenna Gain at Midband, dBi ($\pm .2$ dB)	Receive	38.20 dBi	38.00 dBi	47.40 dBi
	Transmit	42.20 dBi	42.00 dBi	49.20 dBi
VSWR		1.3:1 Max	1.3:1 Max	Rx: 1.5:1 Max Tx: 1.3:1 Max
Pattern Beamwidth (in degrees at midband)	-3 dB	Rx: 2.20° Tx: 1.40°	Rx: 2.20° Tx: 1.40°	Rx: 0.70° Tx: 0.60°
	-15 dB	Rx: 4.90° Tx: 3.10°	Rx: 4.90° Tx: 3.10°	Rx: 1.60° Tx: 1.40°
Sidelobe Envelope, Co-Pol (dBi) 100 λ / D < $\theta \leq 20^\circ$ 20° < $\theta \leq 26.3^\circ$ 26.3° < $\theta \leq 48^\circ$ $\theta > 48^\circ$		29 - 25 Log θ dBi -3.5 dBi 32 - 25 Log θ dBi -10 dBi (averaged)	29 - 25 Log θ dBi -3.5 dBi 32 - 25 Log θ dBi -10 dBi (averaged)	29 - 25 Log θ dBi -3.5 dBi 32 - 25 Log θ dBi -10 dBi (averaged)
Antenna Noise Temperature				
10° Elevation		52 K	57 K	85 K
20° Elevation		46 K	49 K	78 K
30° Elevation		45 K	45 K	73 K
40° Elevation		44 K	45 K	70 K
Cross Polarization Isolation (Linear) On Axis	Receive	>30 dB	N/A	>30 dB
	Transmit	>30 dB	N/A	>35 dB
Axial Ratio (Circular)		N/A N/A	2.28 dB 1.94 dB	N/A N/A
Feed Interface		CPR 229F CPR 137 or Type N	CPR 229F CPR 137 or Type N	WR 75 or Direct Radio Mounting
Maximum Radio Weight (Optional Feed Stabilizer available for higher radio weight)		20 Lbs. (9 Kg.)	20 Lbs. (9 Kg.)	12 Lbs. (5.5 Kg.)

Mechanical

Reflector Material	Glass Fiber Reinforced Polyester SMC
Antenna Optics	Prime Focus, Offset Feed, Four-piece
Mast Pipe Size	6" SCH 40 Pipe (6.63" OD) 16.83 cm.
Elevation Adjustment Range	5° to 90° Continuous Fine Adjustment
Azimuth Adjustment Range	360° Continuous, +/- 10° Fine Adjustment
Mount Type	Elevation over Azimuth
Shipping Specifications	
Shipping Weight (Total):	545 lbs. (248 kg.)
Install (Net) Weight:	365 lbs. (166 kg.)

Environmental Performance

Wind Loading	Operational	50 mph (80 km/h)
	Survival	125 mph (201 km/h)
Temperature Range (operational)	-40° to 140°F (-40° to 60°C)	
Rain (operational)	1/2" (13mm) / hr	
Atmospheric Conditions	Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas	
Relative Humidity	0 to 100% With Condensation	
Solar Radiation	360 BTU/h/ft ²	

GENERAL DYNAMICS

SATCOM Technologies

1500 Prodelin Drive • Newton, NC 28658 USA • Telephone: +1-828-464-4141 • Fax: +1-828-464-4147
Email: vsat@gdsatcom.com • Web Site: www.gdsatcom.com

1000-063 Rev. 08/12