



3.5 Meter Ka-band, K-band Earth Station Antenna

The ASC Signal 3.5 Ka-band earth station antenna provides superior performance and pointing accuracy. The precision one-piece spun aluminum reflector, along with its rugged aluminum and steel construction provide extraordinary strength and precise pointing.

This antenna features a uniquely designed Gregorian sub reflector tracking system which eliminates the need for costly jack drives and large motors.

- Bonded and riveted torsion box for rigidity
- Heavy mounting ring for strength
- Advanced dual reflector Gregorian optics
- Sub reflector closed loop positioning for precise pointing accuracy
- Compliant to ITU 580-5/465-5, FCC 25.209



SPECIFICATIONS

3.5 Meter Ka-band, K-band Earth Station Antenna

Electrical Performance

	Ka-band 4-Port Circular Pol Feed		Ka-band 4-Port Wideband Circular Pol Feed		Ka-band 4-Port Linear Pol Feed		Ka-band 4-Port Linear Pol Feed Eutelsat Freq		K-band 2-Port Linear Pol Feed		K-band 4-Port Linear Pol Feed	
	Rx	Tx	Rx	Tx	Rx	Tx	Rx	Tx	Rx	Tx	Rx	Tx
Frequency (GHz)	20.200- 21.200	30.000- 31.000	18.300- 20.200	28.300- 30.000	17.700- 20.200	27.000- 30.050	21.400- 22.000	27.000- 30.050	10.700- 12.750	17.300- 18.100	10.700- 12.750	17.300- 18.400
Antenna Gain at Midband	55.10 dB	58.50 dB	54.70 dB	58.30 dB	54.30 dB	58.00 dB	55.50 dB	58.00 dB	51.10 dB	54.70 dB	50.90 dB	54.50 dB
Antenna Noise Temperature (Midband, Clear Sky Conditions at 68°F (20°C, Water Vapor Density < 7.5 g/m ³)												
10° Elevation	171 K		145 K		130 K		202 K		44 K		58 K	
30° Elevation	137 K		111 K		96 K		168 K		31 K		45 K	
50° Elevation	130 K		104 K		89 K		161 K		29 K		43 K	
Cross Polarization On Axis	N/A	N/A	N/A	N/A	35 dB	35 dB	35 dB	35 dB	35 dB	35 dB	35 dB	35 dB
Within 1 dB Beamwidth	N/A	N/A	N/A	N/A	35 dB	35 dB	35 dB	35 dB	35 dB	35 dB	35 dB	35 dB
Axial Ratio	0.50 dB	0.50 dB	0.50 dB	0.50 dB	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
VSWR Performance	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1
Port-to-Port Isolation												
Rx to Rx	18 dB		18 dB		35 dB		35 dB		35 dB			
Tx to Rx	85 dB		85 dB		85 dB		85 dB		85 dB			
Tx to Tx	18 dB		18 dB		35 dB		35 dB		40 dB		35 dB	
Waveguide Interface Flange	WR42	WR28	WR42	WR28	WR42	WR28	WR42	WR28	WR75	WR62	WR75	WR62
Tx Power Capacity	500 W/Port		500 W/Port		500 W/Port		500 W/Port		1 kW		750 W/Port	

Mechanical Performance

Optics Type	Dual Reflector, Gregorian
Reflector Material	Precision Formed Aluminum
Reflector Segments	1
Mount Type	Tubular Post Pedestal
Antenna Pointing Range, Course/(Continuous)	
360° Coarse, 30° Steps	
(±24° Continuous)	
0° to 90° Continuous	

Environmental Performance

Operational Temperature	-40°C to 50°C (-40°F to 125°F)
Wind Loading, Survival	150 mph Any Position 88 mph with Ice
Rain	102 mm (4 in per hour)
Solar Radiation	360 BTU/h/ft ² (1135 W/m ²)
Relative Humidity	100%
Shock and Vibration	As Encountered by Commercial Air, Rail and Truck
Atmospheric Conditions	As Encountered by Moderately Corrosive Coastal and Industrial Areas



ASC Signal Corporation
1120 Jupiter Road
Suite 102
Plano Texas 75074 USA

Telephone: +1-214-291-7654

Internet: www.ascsignal.com

All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

ASC-ESA2

© 2012 ASC Signal Corporation