



PRODUCT
SPECIFICATIONS

Detail Photos
(from left to right)
Manual tripod
Pedestal mount
High wind tripod



4.5 Meter Pedestal, Manual Tripod and High Wind Tripod Antennas

Used world-wide in high-density data, voice, communications networks and broadcast applications, the ASC Signal 4.5 meter earth station antenna features an exclusively designed 2 or 4-port prime focus, beam-shaping feed and ground plane configuration.

- 3 year warranty on all structural components
- High gain
- Easy assembly
- Russian Homologation Certificate # OC/1-AO-136

This versatile antenna can be configured in transmit and receive or receive only; either linear or circular polarized; C-band, Ku-band, X-band or hybrid C/Ku receive only. The pedestal mount is manual or motorizable. The standard tripod mount is manual only. The high wind tripod mount is motorizable.



SPECIFICATIONS

4.5 Meter Pedestal, Manual Tripod and High Wind Tripod Antennas

Electrical Performance

	C-band 2-Port Circular Pol Feed		C-band 2-Port Linear Pol Feed		C-band 4-Port Linear Pol Feed		Ku-band 2-Port Linear Pol Feed		X-band 2-Port Circular Pol Feed	
	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit
Frequency (GHz)	3.625-4.200	5.850-6.425	3.625-4.200	5.850-6.425	3.625-4.200	5.850-6.425	10.700-13.250	13.750-14.800	7.250-7.750	7.900-8.400
Antenna Gain at Midband dBi	43.70	46.50	43.80	46.60	43.70	46.50	52.40	53.60	48.20	49.00
Antenna Noise Temperature										
10° Elevation	52 K		47 K		54 K		53 K		45 K	
30° Elevation	39 K		34 K		41 K		41 K		34 K	
50° Elevation	35 K		30 K		37 K		38 K		29 K	
Cross Polarization On Axis	N/A	N/A	30 dB	35 dB	30 dB	35 dB	30 dB	35 dB	N/A	N/A
Within 1 dB Beamwidth	N/A	N/A	30 dB	35 dB	30 dB	35 dB	30 dB	35 dB	N/A	N/A
Axial Ratio	2.30 dB	0.75 dB	N/A	N/A	N/A	N/A	N/A	N/A	1.20 dB	1.20 dB
VSWR Performance	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1
Port-to-Port Isolation										
Rx to Rx	N/A		N/A		40 dB		N/A		N/A	
Tx to Rx	85 dB		40 dB		85 dB		40 dB		20 dB	
Tx to Tx	N/A		N/A		40 dB		N/A		N/A	
Waveguide Interface Flange	Brass CPR-229G	Brass CPR-137G	Alum. CPR-229G	Alum. CPR-137G	Brass CCPR-229G	Brass CPR-137G	Brass WR75	Brass WR75	Alum. WR112	Alum. WR112
Tx Power Capacity	500 W		5000 W		2500 W		2000 W		750 W	

Mechanical Performance

Optics Type	Prime Focus
Reflector Material	Precision Formed Aluminum
Reflector Segments	6
Mount Type	Pedestal Mount, Tripod or High Wind Tripod

Environmental Performance

Operational Temperature	-45.5°C to 52°C (-40°F to 125°F)
Wind Loading (Survival)	
Pedestal or Tripod Mount	with Motor: 125 mph (200 km/h) in Stationary Position without Motor: 125 mph (200 km/h) in Stationary Position
High Wind Tripod Mount	with Motor: 150 mph (240 km/h) in Stationary Position without Motor: 150 mph (240 km/h) in Stationary Position
Wind Loading (Operational)	
Pedestal or Tripod Mount	with Motor: 45 mph (72 km/h) with Gusts up to 65 mph (105 km/h) without Motor: 45 mph (72 km/h) with Gusts up to 65 mph (105 km/h)
High Wind Tripod Mount	with Motor: 100 mph (160 km/h) with > 2 dB Signal Loss @ 6 GHz without Motor: 100 mph (160 km/h) with > 2 dB Signal Loss @ 6 GHz
Rain	102 mm (4 in per hour)
Solar Radiation	1135 Watts/m2 (360 BTU/h/ft2)
Relative Humidity	100%
Shock and Vibration	As Encountered by Commercial Air, Rail and Truck Shipment
Atmospheric Conditions	As Encountered by Moderately Corrosive Coastal and Industrial Areas



ASC Signal Corporation
1120 Jupiter Road
Suite 102
Plano Texas 75074 USA

Telephone: +1-214-291-7654

Internet: www.ascsignal.com

All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

ASC-ESA9
© 2012 ASC Signal Corporation