

Precision SMA Female to 1.85mm Female Adapter



TECHNICAL DATA SHEET

PE9729

Precision SMA Female to 1.85mm Female Adapter

Configuration

Connector 1 SMA Female
Impedance 1 50 Ohms
Connector Specification 1 MIL-STD-348
Connector 2 1.85mm Female
Impedance 2 50 Ohms
Adapter Design Precision
Body Style Straight

Electrical Specifications

Frequency Range, GHz DC to 18
Maximum VSWR 1.3:1

Mechanical Specifications

Temperature

Operating Range,deg C -65 to +125

Size

Length, in [mm] 0.895 [22.73] Width/Dia., in [mm] 0.28 [7.11]

Connector 1

Type SMA Female

Inner Conductor Material and Plating

Beryllium Copper, Gold
Passivated Stainless Steel

Connector 2

Type 1.85mm Female
Inner Conductor Material and Plating Beryllium Copper, Gold
Body Material and Plating Passivated Stainless Steel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-1.85mm-female-straight-adapter-pe9729-p.aspx

Precision SMA Female to 1.85mm Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE9729 CAD DrawingPrecision SMA Female to 1.85mm Female Adapter

