



9.4 Meter Ka-band Earth Station Antenna

The ASC Signal 9.4 Ka-band earth station antenna features Gregorian optics and a fully shaped main reflector. This configuration provides excellent pattern characteristics, high gain and superior pointing accuracy.

A large equipment enclosure with door is located on the pedestal and allows hub mounting of electronic systems.

The ASC Signal 9.4 meter Ka-band antenna is backed by a three year warranty on all structural components.

- Rugged aluminum and steel construction provides high winds survival in any stationary position.
- 3 year warranty on all structural components



SPECIFICATIONS

9.4 Meter Ka-band Earth Station Antenna

Electrical Performance

	Ka-band4-PortWideband Circular Pol Feed Receive Transmit	
Frequency (GHz)	18.300-20.200	28.300-30.000
Antenna Gain at Midband	63.10 dB	66.60 dB
Antenna Noise Temperature (Midband, Clear Sky Conditions at 68°F (20°C, Water Vapor Density < 7.5 g/m3)		
10° Elevation	123 K	
30° Elevation	88 K	
50° Elevation	82 K	
Cross Polarization On Axis Within 1 dB Beamwidth	N/A N/A	N/A N/A
Axial Ratio	0.50 dB	0.50 dB
VSWR Performance	1.30:1	1.30:1
Port-to-Port Isolation		
Rx to Rx	18 dB	
Tx to Rx	85 dB	
Tx to Tx	18 dB	
Waveguide Interface Flange	WR42	WR28
Tx Power Capacity	500 W/Port	

Mechanical Performance

Optics Type	Dual Reflector, Gregorian
Reflector Material	Precision Formed Aluminum
Reflector Segments	16
Mount Type	Pedestal Mount
Antenna Pointing Range	Elevation 5° Coarse, 85° Continuous
	Azimuth 180° Coarse, 120° Continuous
	Polarization ... 180° Coarse, 180° Continuous
Hub/Enclosure Dimensions	Diameter 1.32 m (52 in)
	Depth 1.17 m (46 in)

Environmental Performance

Operational Temperature	-40°C to 50°C (-40°F to 125°F)
Wind Loading (Survival)	with Motor 125 mph (200 km/h) in Stationary Position
	without Motor 125 mph (200 km/h) in Stationary Position
Wind Loading (Operational) ...	with Motor 45 mph (72 km/h) with Gusts up to 65 mph (105 km/h)
	without Motor 45 mph (72 km/h) with Gusts up to 65 mph (105 km/h)
Rain	102 mm (4 in per hour)
Relative Humidity	100%
Shock and Vibration	As Encountered by Commercial Air, Rail and Truck
Atmospheric Conditions	As Encountered by Moderately Corrosive Coastal and Industrial Areas



ASC Signal Corporation
1120 Jupiter Road
Suite 102
Plano Texas 75074 USA

Telephone: +1-214-291-7654

Internet: www.ascsignal.com

All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

ASC-ESA22

© 2012 ASC Signal Corporation