



## 9.4 Meter C-band or Ku-band Earth Station Antenna

This antenna system is used worldwide in broadcast applications and high density data, voice and communications networks.



Like all ASC Signal earth station antennas, the 9.4 Meter Earth Station Antenna provides high gain and exceptional pattern characteristics. The electrical performance and exceptional versatility provides the ability to configure the antenna with your choice of combining network. That versatility is provided at the time of initial purchase, as well as in the future, as your satellite communication requirements evolve. This antenna system is used worldwide in broadcast applications and high density data, voice and communications networks. The ASC Signal 9.4 meter earth station antenna features a computer-optimized dual reflector Gregorian optics system and close-tolerance manufacturing techniques

This combination provides extremely accurate surface contour resulting in exceptionally high gain and closely controlled pattern characteristics. ASC Signal earth station antennas provide maximum durability with minimal maintenance.

- Rugged aluminum and steel construction provides 125 mph (200 km/h) survival.
- 3 year warranty on all structural components.
- Electrical performance meets or exceeds U.S. FCC regulation 25-209, Eutelsat standards and ITU-R, S.580-5 and S.465-5

**SPECIFICATIONS**

**9.4 Meter C-band or Ku-band Earth Station Antenna**

**Electrical Performance**

	Ku-band 2-Port Linear Pol Feed		Ku-band 4-Port Linear Pol Feed		C-band 2-Port Circular Pol Feed		C-band 4-Port Circular Pol Feed		C-band 4-Port Linear Pol Feed	
	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit
Frequency (GHz)	10.700- 5.850- 13.250	13.750- 3.625- 14.800	10.700- 5.850- 12.750	13 14.800	4.200	6.425	.750-3.625- 4.200	6.425	5.850- 3.625- 4.200	6.425
Antenna Gain at Midband, dBi	59.50	60.90	59.20	60.60	50.70	54.40	50.60	54.30	50.60	54.30
Antenna Noise Temperature (Clear Sky Conditions at 20°C (68°F))										
10° Elevation	54 K		70 K		39 K		45 K		45 K	
30° Elevation	39 K		56 K		30 K		36 K		36 K	
50° Elevation	36 K		53 K		29 K		35 K		35 K	

**Mechanical Performance**

Optics Type	Dual-Reflector, Gregorian
Reflector Material	Precision Formed Aluminum
Reflector Segments	20
Hub/Enclosure Dimensions	
Diameter	2.14 m (84 in)
Depth	1.17 m (45 in)
Mount Type	Pedestal Mount
Antenna Pointing Range Course/(Continuous)	
Elevation	0° (90°)
Azimuth	180° (120°)
Polarization	360° (180°)

**Environmental Performance**

Operational Temperature	-45.5°C to 52°C (-40°F to 125°F)
Operational Winds	45 mph (72 km/h) Gusts to 65 mph (105 km/h) (Fixed or Motorized)
Survival Winds	125 mph (200 km/h) (In Stationary Position Fixed or Motorized)
Seismic (Earthquakes)	1 G Vertical and Horizontal Acceleration (8.3 Richter Magnitude and 11 Modified Mercalli Scale)
Rain	102 mm (4 in per hour)
Solar Radiation	1135 Watts/m2 (360 BTU/h/ft2)
Relative Humidity	100%
Shock and Vibration	As Encountered by Commercial Air, Rail and Truck Ship- ment
Atmospheric Conditions	As Encountered by Moderately Corrosive Coastal and



ASC Signal Corporation  
1120 Jupiter Road  
Suite 102  
Plano Texas 75074 USA

Telephone: +1-214-291-7654

Internet: [www.ascsignal.com](http://www.ascsignal.com)

All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

ASC-ESA21  
© 2012 ASC Signal Corporation